# This Page Is Inserted by IFW Operations and is not a part of the Official Record

# **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

# IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problems Mailbox.

Doc. Ref.: AL1

# **PCT**

WORLD INTELLI

#### INTERNATIONAL APPLICATION PUBLISH

(51) International Patent Classification 6:

B01J 19/00, B01F 5/06, B01J 12/00, 14/00, 19/12, 35/04, B01L 3/00

(11) International Publication Number:

WO 96/03206

(43) International Publication Date:

8 February 1996 (08.02.96)

(21) International Application Number:

PCT/US95/09834

A1

(22) International Filing Date:

20 July 1995 (20.07.95)

(30) Priority Data:

08/280,046

25 July 1994 (25.07.94)

US

(71) Applicant: E.I. DU PONT DE NEMOURS AND COMPANY [US/US]; 1007 Market Street, Wilmington, DE 19898 (US).

(72) Inventors: HARBSTER, Kevin, Horning; 80 Brookfield Drive, Fleetwood, PA 19522 (US). PERROTTO, Joseph, Anthony; 136 Pine Hill Road, Landenberg, PA 19350-9166 (US).

(74) Agents: HAMBY, William, H. et al.; E.I. du Pont de Nemours and Company, Legal Patent Records Center, 1007 Market Street, Wilmington, DE 19898 (US). (81) Designated States: BR, JP, KR, RU, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

#### **Published**


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: CHEMICAL MIXING AND REACTION APPARATUS AND PROCESSES FOR THE PREPARATION THEREOF

#### (57) Abstract

An integral structure is provided for chemical processing, particularly high-speed mixing and chemical reacting, in which a plurality of laminae (100, 200, 300) are joined together and having inlet (20, 24) and outlet ports (30, 34) connected by a plurality of intersecting channels formed therethrough which accomodate the passage of one or more chemicals, said laminae (100, 200, 300) comprising a material selected for compatibility with the one or more chemicals, the channels being formed so that chemicals are combined at intersections therein at sufficient angles of attack and shear rates so that chemical reactions are not limited by mass transfer. Chemicals are introduced through the inlet ports (29, 24) and processed along the channel, with desirable product withdrawn through the outlet ports (30, 34). The laminae are selected from material of groups III, IV or V of the Periodic Table. Processes of manufacture of the apparatus and processes utilizing the apparatus are also disclosed herein.



## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE .	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	haly	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belanus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgystan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic	SD	Sudan
CG	Congo		of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SI	Slovenia
CI	Côte d'Ivoire	KZ	Kazakhstan	SK	Slovakia
CM	Cameroon	ũ	Liechtenstein	SN	Senegal
CN	China	LK	Sri Lanka	TD	Chad
cs	Czechoslovakia	LÜ	Luxembourg	TG	Togo
cz	Czech Republic	LV	Latvia	TJ	Tajikistan
DE	Germany	MC	Monaco	TT	Trinidad and Tobago
DK	Denmark	MD	Republic of Moldova	ÜA	Ukraine
ES	Spain	MG	Madagascar	US	United States of America
FI	Finland	ML	Mali	UZ	Uzbekistan
FR	France	MN	Mongolia	VN	Vict Nam
GA	Gabon	****	1.101.84	•••	* ****

#### TITLE OF THE INVENTION

# CHEMICAL MIXING AND REACTION APPARATUS AND PROCESSES FOR THE PREPARATION THEREOF FIELD OF THE INVENTION

This invention relates to an integrated chemical processing apparatus, adapted for use with high-speed chemical reactions, which can be incorporated into a larger integral structure of multiple chemical processing units or an integrated system. More particularly, the present invention is directed to chemical processing apparatus characterized by improved rapid mixing of chemicals passing therethrough, by enhanced safety of operation, and by reduced capital investment.

#### 15 BACKGROUND OF THE INVENTION

To achieve efficient chemical processing, it is necessary to precisely control a number of processing parameters, such as temperature, pressure, mixing conditions, exposure of reactants to catalyst material, exposure of reactants to products and/or byproducts and exposure of reactants to actinic radiation. Certain chemical reactions are particularly difficult to perform in an optimal manner because the chemical reactions occur very quickly, sometimes before the reactants are completely mixed together. Certain non-stoichiometric portions of the partially mixed reactants may cause reaction products other than those desired to be produced.

Conventional chemical processing equipment

typically holds a relatively large volume of materials and consequently has a relatively large volume to surface area ratio, and are thus particularly ill-suited for high speed chemical reactions. Different portions of the reactant materials contained within such

processing equipment are more likely to be exposed to

15

20

25

30

35

different histories of conditions. In the case of a conventional tank reactor, for example, when reactants are introduced they are typically added in separate streams, usually at controlled rates, and are then mixed together. The so-called T-mixer has been used to mix incoming streams together before they enter a reactor tank. For chemical reactions that occur rapidly, i.e., typically in less than one second, insufficient mixing may have occurred, even with use of the T-mixer, before the reaction is well established. Portions of the incompletely mixed mixture may be starved of one or the other reactant and undesired secondary reactions may occur which produce undesired byproducts.

Rapid stirring of the reactants may reduce this mixing history difference, but will not eliminate it. As a result of the nonhomogeneous mixing history, different portions of the reactants may chemically react differently. Undesired reactions may occur in portions of the reactants that cause localized heating in these different portions. This localized heating may accelerate undesired reactions. This may result in the production of undesired waste products, which may be hazardous and/or which must be properly disposed of. In extreme situations, reaction rates may accelerate to uncontrollable levels, which may cause safety hazards, such as potential explosions.

If, however, the volume in each reactant stream being mixed is substantially reduced, then the speed of mixing of the reactants may be greatly increased to substantially improve the control of homogeneity of mixing history of the reactants.

It has been recognized that a high degree of flow turbulence enhances the ability to rapidly mix two or more reactants together. Rapid mixing is known to be important for rapid chemical reactions. A high degree of turbulence is also known to enhance heat transfer as well as mixing rates. Thus a structure having both a low contained volume and a high degree of flow turbulence is particularly advantageous for precise control of high-speed chemical reactions.

· Mixer assemblies having highly turbulent flow have been constructed by machining the desired passages and chambers in metal plates, using conventional metalworking techniques, and then assembling the plates into a stack and either clamping the stack together or 10 permanently joining the stack, as by welding or soldering. An example is U.S. Patent 3,701,619. Structures formed using conventional machine tool techniques cannot economically achieve volume to surface area ratios that are very low. The materials of construction of conventional chemical processing apparatus, such as steel and specialty iron alloys, furthermore may be subject to corrosion and wear, may have undesirable effects on catalytic activity, or may 20 "poison" a catalyst.

It is an object of the present invention to provide a chemical processing unit that mixes reactants in a rapid and efficient manner, such that chemical reactions are not limited by mass transfer considerations. 25 present invention provides the capability to integrate one or more mixing/reaction units with control elements into a larger integrated chemical processing system to meet the needs of a specific high-speed chemical reaction. 'A feature of the present invention is that it can be economically used in the laboratory, to make a 30 range of precise sizes of mixing/reaction units, to perform the basic chemical reactions for determining the optimum operating parameters. Commercial production volumes may then be readily achieved by replicating the

15

20

30

mixing/reaction units and operating them in parallel in a larger integrated chemical processing system.

Advantages of the present invention, when used in a larger integrated chemical processing apparatus, include the elimination of many interconnections and joints, thereby reducing the potential for leaks. These and other objects, features and advantages will become better understood upon having reference to the following description of the invention.

#### SUMMARY OF THE INVENTION

There is disclosed and claimed herein an apparatus for use in an integral structure for chemical mixing and reacting of one or more chemicals, comprising a plurality of laminae joined together and having a plurality of intersecting channels formed therethrough which accommodate the passage of one or more chemicals. The laminae comprise a material selected for compatibility with the one or more chemicals, the channels being formed so that chemicals are combined at intersections therein at sufficient angles of attack and shear rates so that chemical reactions are not limited by mass transfer considerations. Moreover, the shear rate is sufficient to disrupt boundary layer formation. The channels are arranged such that two or more channels are positioned at a point of intersection to form an angle of attack of from 20 to 160 degrees, preferably from 70 to 110 degrees, and most preferably about 90 degrees.

The apparatus of the invention may be prepared according to the process of the invention. The process comprises first, processing a plurality of laminae each having a top portion and a bottom portion and a desired thickness, sufficient to form desired pathways thereon or therethrough. The laminae are then stacked and

15

20

25

30

bonded together in precise alignment to develop channels that intersect at a desired angle of attack.

In the process for preparing the integral structure, the pathways on facing surfaces of adjacent laminae generally form passages through the structure in the plane of the laminae having the desired cross-sectional areas. These planar passages are connected with each other and with passages orthogonal to the plane of the laminae which pass through one or more laminae to form passages having the desired overall three-dimensional shapes.

The apparatus of the present invention may be used in a method for mixing and reacting of chemicals. The method comprises: (a) introducing one or more chemicals into channels of the above-described structure; (b) directing the chemicals to traverse the channels; (c) coordinating traversal at a traversal rate so that angles of attack and shear rates are sufficient to insure that chemical reactions are not limited by mass transfer considerations; and (d) withdrawing reacted product from the channels of the structure.

The invention can be more fully understood from the following detailed description thereof in connection with accompanying drawings.

## BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a perspective view of an apparatus of the present invention.

Figure 2 is an exploded perspective view of the apparatus, as seen from above, showing the top surfaces of three laminae which are used to form the structure.

Figure 3 is an exploded perspective view of the apparatus, as seen from below, showing the bottom surfaces of three laminae which are used to form the structure.

10

25

30

Figure 4 is an enlarged first sectional view, taken along section lines 4-4 of Figure 1.

Figure 5 is an enlarged second sectional view, taken along section lines 5-5 of Figure 1.

Figure 6 is an exploded perspective view of a portion of the apparatus of Figure 1, showing the bottom surface of a first lamina 100 and the top surface of the second lamina 200. Figures 6, 8, 9 show a first embodiment arrangement of channels that form an array of mixing elements and a distribution manifold.

Figure 7 is an exploded perspective view of the bottom of a second lamina 200 and the top of a third lamina 300 showing channels that form a distribution manifold.

Figure 8 is an enlarged view of the portion of Figure 6 designated as 8-8 showing mixing element 64A2.

Figure 9 is an enlarged view of a portion of Figure 8 designated as 9-9.

Figure 10, which corresponds in scale to Figure 9, shows a second embodiment arrangement of channels that form an array of mixing elements and a distribution manifold.

Figure 11 is a simplified perspective view which illustrates the channels of Figure 8 and the intersections of those channels.

Figure 12 is a simplified perspective view which illustrates the channels of Figure 10 and the intersections of those channels.

Figure 13a-c is a plan view of the channels of Figure 9 showing the channels separately and superimposed.

### DETAILED DESCRIPTION OF THE INVENTION

The present invention is characterized by small channels of complex three-dimensional shapes which:

35 (1) can create a high degree of flow turbulence that

enhances rapid mixing and heat transfer; (2) intersect with other channels in a shearing fashion at a predetermined angle of attack; (3) have a very low volume to surface area ratio that minimizes temperature gradients and further enhances heat transfer; and (4) controls residence time of materials therein, to achieve more precise temperature control, and a more uniform temperature history, for every portion of the entire volume of reactants mixed and reacted. Channels small enough that they will not allow the propagation of a flame may be readily formed and thus can be used to safely react potentially explosive chemical reactants. The channels may measure as small as about 10 micrometers in cross section.

15 Throughout the following detailed description, reference characters between 1 and 99 refer to overall features of the invention. That is, these features may only be apparent on joinder of adjacent laminae. For example, in Figure 7 chamber 50M is comprised of chamber 20 250M on laminae 200 and chamber 350M on laminae 300. Laminae are numbered 100, 200, 300, and specific features on each respective lamina are numbered 101 to 199, 201 to 299, etc. with the last two digits corresponding to the overall feature of the invention. 25 The suffix letter "V" is used to designate interlamina vertical pathways, also known as "vias", through the structure. Similary, suffix "M" indicates a manifold chamber within a manifold; suffixes "S" and "T" indicate straight and turning portions of pahtways. Suffixes comprising a hyphen and numeral (-1, -2, etc.) are used 30 to designate parts of specific elements, such as individual branches of the branched manifolds. A capital letter and number are appended to the reference character to designate elements of an array (e.g., mixer 35 64A2 of array 64). Numerals enclosed in curved braces

15

20

25

() designate crystal planes in a crystalline material (e.g., (100)).

Referring to Figure 1, there is shown an apparatus 10 exemplary of the present invention. This apparatus 10 is comprised of a plurality of laminae 100, 200, 300 fused together to form an integral structure. One or more inlet ports (here, inlet ports 20 and 24 are shown) enable the flow of reactants into the apparatus and one or more outlet ports (here, outlet ports 30 and 34 are shown) enable the flow of the resulting reaction products out of the apparatus. It is to be appreciated that the inlet ports 20 and 24 and outlet ports 30 and 34 do not necessarily have to be positioned only through lamina 100 as shown but may extend through all three laminae (e.g., outlet port 34 in Figure 4). These elements could be arranged to meet the integral structure at the side of a lamina, for example (not shown). The laminae may be comprised of either the same or different materials. The laminae (also known as wafers) 100, 200, 300 preferably are comprised of materials from groups III, IV or V of the Periodic Table, silicon being the most preferred material. If desired one or more of the laminae may be comprised of an alternate material, such as ceramic, a glass material such as Pyrex or other compatible materials.

Figure 2 shows the top surfaces of the three laminae 100, 200, 300 and Figure 3 shows the bottom surfaces of the three laminae 100, 200, 300 which are used to form the apparatus of Figure 1. Operative features of the apparatus shown in Figures 2 and 3 are: two inlet distribution manifolds 40, 44 formed by pathways in the bottom surface of lamina 100 and the top surface of lamina 200; an array 60 of mixer/reaction chambers represented by a series/parallel arrangement of T-mixers 62 and intersecting-channel mixing elements 64

15

formed by corresponding pathways in the bottom surface of lamina 100 and the top surface of lamina 200; a fork-shaped outlet collection manifold 50 formed by corresponding pathways in the bottom surface of lamina 200 and the top surface of lamina 300.

In sectional views of Figures 4 and 5 the vertical scale is exaggerated for clarity of illustration. Although the laminae of the apparatus are fused into an integral structure when completely fabricated, for clarity of illustration the interfaces between the laminae are shown in Figures 4 and 5.

In Figures 4 and 5, which illustrate typical flow passages in the interior of the structure, the vertical pathways 20V, 24V, 30V, 34V which connect respectively with the inlet ports 20, 24 and outlet port 30 in lamina 100 and outlet port 34 in outer laminae 100 and 300, are typically formed by grinding or drilling through the lamina.

In Figure 4 three passages 40-1, 40-2, 40-3, which are branches of distribution manifold 40 and three passages 44-1, 44-2, 44-3, which are branches of distribution manifold 44 are formed in the top surface of lamina 200. Five passages 50-1, 50-2, 50-3, 50-4, 50-5, which are branches of collection manifold 50, are respectively formed by corresponding mirror image pathways 250-1, 250-2, 250-3, 250-4, 250-5 (see also Figure 7) in the bottom surface of lamina 200 and pathways 350-1, 350-2, 350-3, 350-4, 350-5 (Figure 7) in the top surface of lamina 300.

In Figure 5 the central axis of a third horizontal passage 50-3 (see also Figure 8), which comprises the center branch of a 5-branch collection manifold 50, lies in the plane of the sectional view. The horizontal passage 50-3 is formed by corresponding mirror image pathways, respectively pathway 250-3 (Figure 7) in the

10

15

20

25

30

bottom surface of lamina 200 and pathway 350-3 (Figure 7) in the top surface of lamina 300. The passages which comprise the 5-branch collection manifold 50 in the exemplary apparatus are formed using an etching technique.

In Figure 5 passages 160A, 160B, 160C, 160D, in combination with the branches 40-1, 44-1; 44-1, 40-2; 40-2, 44-2; and 40-3, 44-3 of distribution manifolds 40, 44 (Figures 4 and 7) form an array of T-mixer structures 62 whose operation will be subsequently described in conjunction with Figures 6, 7. The passages 164 in the bottom surface of the lamina 100 and the passages 264 in the top surface of lamina 200 cooperate to form an array of mixing chambers 64, each of which comprises a plurality of intersecting channels (Figure 6).

At the left of Figure 5 is vertical passage 20V, which extends through lamina 100 to connect inlet port 20 with the common chamber 40M of manifold 40. At the right of Figure 5 is vertical passage 24V, which extends through lamina 100 to connect inlet port 24 with common chamber 44M of manifold 44. A third branch 50-3 of 5-branch manifold 50 is formed by corresponding mirror image pathways 250-3 and 350-3 (Figure 7) in the bottom surface of lamina 200 and the top surface of lamina 300, respectively. Mixing chambers 64A3, 64B3, 64C3, 64D3 are visible in Figure 5.

Figure 6 shows an arrangement of pathways that cooperate to form an array of mixer/reaction chambers 60 and a pair of distribution manifolds 40, 44. First distribution manifold 40 is comprised of common chamber 40M and branch passages 40-1, 40-2, 40-3. The chamber 40M is formed by the combination of chamber 140M, on the bottom surface of the first lamina 100, and chamber 240M on the top of lamina 200. Also shown is the opening of

vertical pathway 20V which connects input port 20 with the common chamber 40M.

Second distribution manifold 44 is comprised of common chamber 44M and branch passages 44-1, 44-2, 44-3. The chamber 44M is formed by the combination of chamber 144M, on the bottom surface of the first lamina 200, and chamber 244M on the top of lamina 200. Also shown is the opening of vertical pathway 24V which connects input port 24 with the common chamber 44M.

A series of serpentine pathways 164 are formed on 10 the bottom surface of the first lamina 100, which cooperate with corresponding serpentine pathways 264 of lamina 200, to form the array of intersecting-channel mixing elements 64 (here, 64A5 formed from 164A5 and 264A5 in Figure 6) of the mixer array 60. The mixer 15 array 60 comprises multiple groups 60A (e.g., 64A1-64A5), 60B, 60C, 60D of multiple parallel mixers In the specific example shown, there are five mixers in each group, that are respectively designated 64A1, 64A2, 64A3, 64A4, 64A5 through 64D1, 64D2, 64D3, 20 64D4, 64D5. Figure 6 also shows chambers 40M and 44M, previously mentioned.

Each mixer 64 is comprised of two serpentine pathways, a first pathway 164 formed on the bottom of the first lamina 100 and a second pathway 264 formed on 25 the top of the second lamina 200. The first and second pathways are each comprised of a series of straight segments and turning segments connected together to form a continuous path. The first and second pathways are positioned on abutting surfaces with the segments 30 longitudinally offset such that the corresponding turning segments intersect repeatedly. The mixer element 64 (as illustrated by mixer element 64A2) may be described as having a double serpentine path (best seen in Figure 11).

WO 96/03206

Four pathways 160A, 160B, 160C and 160D, cooperate respectively with branches 40-1, 40-2, 40-3 of manifold 40, branches 44-1, 44-2, 44-3 of manifold 44 and a first straight segment 264S of each serpentine pathway 264 to form a series of T-mixers 62 (best seen in Figure 7). Each first straight segment 264S thus connects each T-mixer 62 with each serpentine mixer 64 of mixer array 60.

Figure 7 shows the arrangement of pathways that 10 cooperate to form a collection manifold 50. As seen in Figures 6 and 7, collection manifold 50 is comprised of common chamber 50M and branch passages 50-1, 50-2, 50-3, 50-4, and 50-5. The vertical pathways 64A1V, 64A2V, 64A3V, 64A4V, and 64A5V connects the last segment of mixer 64A1, 64A2, 64A3, 64A4, 64A5 with the collection 15 manifold branches 50-1, 50-2, 50-3, 50-4, and 50-5, respectively; the vertical pathway 64B1V, 64B2V, 64B3V, 64B4V, and 64B5V connects the last segment of mixer 64B1, 64B2, 64B3, 64B4, 64B5 with the collection manifold branches 50-1, 50-2, 50-3, 50-4, and 50-5, 20 respectively; the vertical pathway 64C1V, 64C2V, 64C3V, 64C4V, and 64C5V connects the last segment of mixer 64C1, 64C2, 64C3, 64C4, 64C5 with the collection manifold branches 50-1, 50-2, 50-3, 50-4, and 50-5, respectively; and the vertical pathway 64D1V, 64D2V, 25 64D3V, 64D4V, and 64D5V connects the last segment of mixer 64D1, 64D2, 64D3, 64D4, 64D5 with the collection manifold branches 50-1, 50-2, 50-3, 50-4, and 50-5, respectively. Vertical passage 30V connects collection manifold 50 with the outlet port 30 on the first side of 30 lamina 100. Vertical passage 34V connects manifold 50 with both outlet ports 34 on the first side of lamina 100 and the second side of the lamina 300, as best seen in Figure 5.

------

As best seen in Figure 8, each pathway 160 cooperates with manifolds 40 and 44 and a first straight segment of serpentine pathway 264 to form a T-mixer 62. This connects with a serpentine mixer 64, comprised of the multiple straight segments 264S and turning segments 264T. As also may be seen in Figure 8 each portion of pathway 160, e.g., portion 160A-1 between manifold 40-1 and segment 264S1 and portion 160A-2 between manifold 44-2 and segment 264S1, may be of a different cross-10 sectional size to provide the desired flow rate of each chemical being mixed. The number of straight and turning segments 164S, 164T and 264S, 264T and the cross-sectional size of each segment of 164 and 264 may be selected, according to the mixing requirements and 15 flow characteristics of the chemicals being processed. As seen in Figure 9 the serpentine pathways 164, 264 are comprised of straight segments designated with a suffix letter "S" (171S, 172S, 173S, 174S, 175S, and 271S, 272S, 273S, 274S, 275S) and turning segments designated with a suffix letter T (171T, 172T, 173T, 20 174T, 175T, and 271T, 272T, 273T, 274T, 275T). Corresponding turning segments (e.g., 171T, 271T) of pathways 164 and 264 intersect in a shearing fashion at a ninety (90) degree angle of attack. By slightly 25 offsetting the position of pathway 164 relative to pathway 264 this angle of attack may be changed if desired. By rotating lamina 100 relative to lamina 200,

and suitably altering the spacing of the straight segments (suffix S) and turning segments (suffix T),

30 almost any desired angle of attack may be achieved.

Angles of attack within the range of 20 degrees to 160 degrees may be readily realized, as is contemplated being within the scope of this invention.

Figure 10 shows an alternate arrangement of channels, which may be used in place of the arrangement

30

35

shown in Figures 6, 8, and 9. Figure 10 shows two channels 181, 182 in the bottom surface of lamina 100 that join at a point of intersection, traverse in a combined configuration as channel 183, are subsequently separated into two channels 184, 185, and then recombined as channel 186, separate into channels 187, 188. Channel 281 in the top surface of lamina 200 separates at a point of intersection into two channels 282, 283, which are then recombined as channel 284, are subsequently separated into two channels 285, 286, and then recombined as channel 287. Channel 181 intersects with channel 282 and channel 182 intersects with channel 283 at predetermined angles of attack and shear rates. Similarly channel 184 intersects with channel 282, 15 channel 185 intersects with channel 283, channel 184 intersects with channel 286, channel 185 intersects with channel 287, channel 187 intersects with channel 286, channel 188 intersects with channel 287.

Figure 11 depicts the channels of Figure 9 in a 20 somewhat simplified manner to better visualize the shape, relative position and intersections of the channels. As may be appreciated from Figures 9 and 11, two channels repeatedly intersect to form a double helix configuration, wherein a first channel 164 is comprised 25 of straight segments and turning segments in a first plane, a second channel 264 is comprised of straight segments and turning segments in a second plane.

Chemicals within a first channel are repeatedly subjected to the sequence of: (a) a turbulent left hand turn, (b) a turbulent left hand shearing intersection with chemicals in a second channel, (c) a turbulent right hand turn, (d) a turbulent right hand turn, (e) a turbulent right hand shearing intersection with chemicals in the second channel, (f) a turbulent left hand turn.

15

20

25

30

35

Figure 12 depicts the channels of Figure 10 in a somewhat simplified manner to better visualize the shape, relative position and intersections of the channels. In this figure it can be seen that the two channels intersect at angles of attack and shear rates. Each channel comprises two or more channels that join at a point of intersection, traverse in a combined configuration, are subsequently separated into two or more channels, and then subsequently rejoin.

Figure 13(a)-(c) is a plan view of the channels of Figure 9. It shows channel 164 alone (Figure 13(c)), chanel 264 alone (Figure 13(a)), and 164 superimposed with 264 (Figure 13(b)). At the point of intersection of the channels a centerline 164C of channel 164 and a centerline 264C of channel 264 are shown. The included angle  $\alpha$  between these centerlines is defined as the "angle of attack" of the two channels.

Multiple units of the chemical mixing and reaction apparatus can be used in sequence or in tandem. The incorporation of units in any number of sequential or tandem patterns is a design choice to be made by those skilled in the art and according to the desired chemical processing result.

As seen in Figures 9 and 10 the particular angles of the channel walls produced at the turning sections (e.g., 171T) are due to the orientation of the crystal planes of the silicon. In the illustrated example each lamina comprises a silicon wafer which has the major planar surface of the wafer in the (100) crystal plane. The sides of the straight segments (e.g. 171S, 271S) are aligned to be in the (110) crystal planes. When etched with an anisotropic etch, the major sides of the segments are bevelled from the vertical at a 57 degree angle and are in the (111) crystal planes. The outside corners between the straight segment 171S and the

10

turning segment 171T, are not sharp right angles but are beveled by two so-called bevelling faceting planes, which are the {210} crystal planes, thus producing the bevelled corners which are best seen in Figures 9 and 10.

#### FABRICATION OF THE APPARATUS

The apparatus of the present invention is achieved by a multi-step fabrication process. First, a series of planar laminae or wafers, are processed to form desired patterns of pathways on one or both major surfaces of each lamina or through the thickness of the lamina. The laminae are then joined together to form a plurality of intersecting channels that accommodate the passage of chemicals.

15 In the preferred embodiment of the figures, the laminae are arranged and precisely oriented to locate the channels in adjacent laminae. These channels may be continuous or discontinuous along each of the laminae. Discontinuous channels are continuously aligned between 20 adjacent laminae sufficient to form a continuous pathway therethrough. A typical channel is comprised of straight segments and turning segments in a first plane, straight segments and turning segments in a second plane and transition segments between the two planes. 25 straight or turning segments of a channel may be formed as a groove or trough entirely within one lamina. When assembled this groove cooperates with the facing planar surface of the adjacent lamina to close the crosssection of the channel. This is best illustrated by the cross-sectional view of distribution manifold 40 (seen 30 as 40-1, 40-2, and 40-3) in Figure 4. Mirror image grooves or troughs on facing surfaces of adjacent laminae may cooperate to form a channel having a symmetrical cross-section. This is best illustrated by 35 the cross-sectional view of collection manifold 50 (seen as 50-1, 50-2, 50-3, 50-4, and 50-5) in Figure 4. The transition segments of the channels may be passages that pass through a lamina to connect a channel segment on a first lamina with another segment on a second lamina or with a distribution or collection manifold. This is best illustrated by the cross-sectional view of vertical pathways 64A3V through 64D3V in Figure 5.

The processing of the laminae to form pathways may 10 be performed by a procedure selected from the group of: subtractive processes, additive processes, and forming processes. Subtractive processes comprise chemical etching, electrochemical machining (ECM), electrical discharge machining (EDM), laser ablation, drilling and cutting, abrasive grinding and single diamond point 15 cutting (such as used to fabricate ceramic parts). Additive processes comprise deposition processes, such as electroforming, selective plating, chemical vapor deposition, stereo lithographic photoforming, and 20 welding. Forming processes comprise molding, casting, and stamping. Wear resistant coatings, such as metalloid carbides, in the form of thin films, may be optionally deposited on the processed laminae before

#### 25 Materials of Construction

bonding.

30

35

Selection of lamina materials is based upon the material's compatibility with the chemicals to be mixed and reacted. As used herein "compatibility with the chemicals to be mixed and reacted" includes without limitation: resistance to chemical degradation; operating conditions, such as temperature and pressure; thermal conduction requirements; required features to be created in the lamina, including size, geometrical shape and precision; the sealability of the lamina material; and economic considerations.

15

20

A variety of materials, may be used to construct the mixing/reaction units of the present invention. Crystalline materials that can be processed using photolithographic techniques may be used, especially when a mixing/reaction unit with extremely small crosssectional passages are desired, for instance when gasses that react rapidly are to be processed. crystalline materials would typically include elements from groups III through V of the periodic table, for example silicon. Other compound materials, selected for their resistance to chemical attack, may be used to fabricate the laminae or may be used as coatings on the laminae. Ceramic materials may be used, such as silicon carbide, tungsten carbide, alumina and sapphire for instance using known molding, pressing and sintering techniques, to form the laminae. Thin films may be deposited on the surfaces of the laminae, such as by chemical vapor deposition techniques, to improve resistance of the passages to chemical attack or to facilitate bonding of the laminae. Glass materials, such as fused quartz, pure silica glass and borosilicate glass, as well as composite materials, such as ceramic composites and polymeric composites may be used.

for example, wafers similar to those used to

fabricate semiconductor electronics components, such as
single crystal silicon wafers, may be used. For such
silicon wafers a combination of subtractive techniques
may be used to form the passages. The laminae are
subsequently stacked in precise alignment and joined

together (as by bonding or clamping) into an integral
structure. As illustrated in the example of Figure 1,
three laminae are joined as an apparatus. The laminae
may be of identical or different materials. The outer
laminae may be silicon or a protective material such as
metal, ceramic, composite material or glass while the

inner lamina would typically be silicon. If all the laminae are silicon, thermal fusion bonding is a preferred method of joining the laminae because the strength of the bond achieved approaches that of the laminae themselves.

### OPERATION OF THE APPARATUS

Having reference to Figures 1-3, the two materials to be reacted flow into the unit through input ports 20, 24, through vertical passages 20V, 24V into distribution manifolds 40, 44 and into mixer array 60. Optional temperature control means (not shown) may be used to maintain the mixer array 60 at the desired temperature. The mixed material is collected in collection manifold 50 and passed through vertical passage 30V to the outlet port 30 or through vertical passage 34V to the outlet port 34.

Additional microfabricated process control elements, such as proportional valves, pressure, temperature and flow sensors, may be incorporated with the structure of the present invention. These elements, when used with external controls could regulate the flow of reactants within the integrated chemical processing unit and thus control the residence time. Any rapid chemical process, such as hydrolysis, nitration, polymerization, and oxidation may be practiced using the integrated structure of the present invention.

#### FABRICATION OF THE LAMINAE

In the preferred embodiment, most steps of the fabrication process generally correspond to known

30 semiconductor processing techniques for silicon wafers. The photo-tools for the patterns for each side of each wafer are prepared using well known computer-aided-design techniques. Already polished silicon wafers, having the {100} crystal plane and other orientations on the major surfaces may be purchased from commercial

20

25

The polished wafers are first cleaned using a well-known general cleaning technique, such as the "RCA process". An oxide film is grown on the wafer using well-known standard techniques. A nitride layer is deposited over the oxide layer using a known chemical vapor deposition method. The nitride layer protects the oxide layer from attack by the etch used to etch the silicon. A photoresist is applied, following the directions of the photo resist manufacturer, using the well-known spin coating technique.

The desired pattern is formed by first masking the wafer with a photo-tool having an image of the desired pattern, which is precisely aligned with the crystal planes of the wafer. Straight portions of the pattern are typically aligned along the {110} crystal plane. 15 After exposing and developing the photoresist, the undeveloped photoresist is stripped to expose part of the nitride/oxide film layer. The exposed nitride/oxide film is finally etched to form an nitride/oxide film negative image of the desired pattern.

The pathways are formed in the surfaces of the wafers by etching the silicon, using either isotropic or anisotropic etch, the choice of which is dependent on the shape of the pathway desired. Curved shapes are etched using an isotropic etch. Straight shapes may employ either etch, depending on the desired crosssectional shape pathway. If a trapezoidal cross-section is desired an anisotropic etch is used.

If a given wafer is to be etched on both major 30 surfaces using the same etch, both sides of the wafer may be masked with resist, the resist exposed with the desired pattern on each surface, developed, washed and the nitride/oxide etched simultaneously on both surfaces. Then the silicon may be simultaneously etched 35 on both surfaces. If different types of etchants are to

be used on each side of the wafer, all steps for the first etch are completed and then the steps are repeated for the second etch. After all the etching steps have been completed the vertical passages or vias through the wafer are formed by laser cutting through the wafers, typically using a pulsed neodymium-YAG laser cutting system. After laser cutting, the wafers are again recleaned to remove cutting debris. The remaining nitride layer of the negative image is removed from the wafer, by using a suitable solvent, such as boiling 10 phosphoric acid, exposing the undamaged oxide layer. The remaining oxide layer negative image may optionally be removed from the wafer, by using a suitable solvent, such as buffered hydrogen fluoride. The wafer is recleaned, using the technique as described above. 15

Other techniques may be used which are dependent upon the lamina material. Laminae which are comprised of group III, IV or V material are processed using etching, grinding, drilling and polishing techniques. Laminae comprised of glass, Pyrex, or fused silica are 20 fabricated using conventional glass cutting, drilling, grinding, and polishing techniques. Laminae comprised of ceramic materials may be formed by slip casting, consolidated by pressing and fired using well known 25 techniques.

When all the laminae have been individually processed the laminae are carefully stacked in a precisely aligned manner and fusion bonded. To achieve good bonding of silicon laminae, the surfaces should be highly planar and the oxide layers on each surface 30 should be undamaged. Since silicon is somewhat transparent in the infrared, a microscope with an infrared video camera may be used, with optional alignment indicia on each wafer, to insure precise alignment of the wafers before they are fusion bonded.

If an outer lamina is comprised of glass, this lamina is then anodically bonded to the already fused stack of inner laminae.


Those skilled in the art, having the benefit of the teachings of the present invention as hereinabove set forth, can effect numerous modifications thereto. It is readily appreciated that such modifications can be made without departing from the spirit of the scope of the present invention. Accordingly, such modifications are to be construed as being encompassed within the scope of the present invention as set forth in the appended claims.

#### CLAIMS


1. An apparatus for use in an integral structure for chemical mixing and reacting of one or more chemicals, comprising a plurality of laminae joined together and having a plurality of intersecting channels formed therethrough which accommodate the passage of one or more chemicals,

said laminae comprising a material selected for compatibility with the one or more chemicals,

- said channels being formed so that chemicals are combined at intersections therein at sufficient angles of attack and shear rates so that chemical reactions are not limited by mass transfer considerations.
- 2. The apparatus of Claim 1 wherein the channels are generally planar, a first channel being disposed in a first plane and a second channel being disposed in a second plane, wherein the first and second planes are parallel and adjacent to each other, and the channels are generally serpentine and are offset from each other such that the first and second channels repeatedly intersect in a shearing fashion and form angles of attack at points of intersection.
- 3. The apparatus of Claim 2 wherein two or more channels are positioned at a point of intersection to form an angle of attack of 20 to 160 degrees.
  - 4. The apparatus of Claim 3 wherein the angle of attack is 70-110 degrees.
- 5. The apparatus of Claim 3 wherein the angle of attack is 90 degrees.
  - 6. The apparatus of Claim 1 wherein shear rate is sufficient to disrupt boundary layer formation.
- 7. The apparatus of Claim 1 wherein two or more channels intersect at aforesaid angles of attack and shear rates, each channel comprising two or more



SUBSTITUTE SHEET (RULE 26)






FIG.6

SUBSTITUTE SHEET (RULE 26)




FIG.7

SUBSTITUTE SHEET (RULE 26)




FIG.8




FIG.9






FIG. 10





**SUBSTITUTE SHEET (RULE 26)** 


11/12



SUBSTITUTE SHEET (RULE 26)







SUBSTITUTE SHEET (RULE 26)

Inter onal Application No PCT/US 95/09834

<u> </u>				, 00 30, 0300 ;	
IPC 6	SIFICATION OF SUBJECT MATTER B01J19/00 B01F5/06 B01 B01J35/04 B01L3/00	lJ12/00	B01J14/00	B01J19/12	
According	to International Patent Classification (IPC) or to both nation	Inal classification	and IPC		
B. FIELD	OS SEARCHED				
Minimum IPC 6	documentation searched (classification system followed by o BOIJ BOIF BOIL	classification syn	nbols)		
Document	ation searched other than minimum documentation to the ext	tent that such do	cuments are included in 6	the fields searched	<u> </u>
Electronic	data base consulted during the international search (name of	data base and, t	where practical, search te	rms used)	
C. DOCUM	MENTS CONSIDERED TO BE RELEVANT				
Category *	Citation of document, with indication, where appropriate,	of the relevant p	rate.	Relevant to claim	No.
<b>A</b>	US,A,5 252 294 (MESSERSCHMIT) GMBH) 12 October 1993 see abstract see figures 1-9,15	T-BÖLKOW-	BLOHM	1	
•	see claims 1-8,15				
۸	FR,A,2 640 620 (INSTITUT FRAM PÉTROLE) 22 June 1990 see abstract	ÂAIS DU		1	
	see page 1, paragraph 1 see page 2, paragraph 2 - pag paragraph 2				
	see page 9, paragraph 5 - pag paragraph 3 see figures 1-3	je 10,			
		-/			
ļ		•	•		
X Furd	her documents are listed in the communition of box C.	X	Patent family members a	ure listed in annex.	
	tegories of cited documents:			er the international filing date	
coura qu	ent defining the general state of the art which is not ered to be of particular relevance document but published on or after the international	ale เกพ	ed to understand the principles	onflict with the application but aple or theory underlying the	
iniug c	date ent which may throw doubts on priority claim(s) or	· can	mot be considered novel o	ance; the claimed invention or cannot be considered to en the document is taken alone	
arrigo. Marca	is cited to establish the publication date of another in or other special reason (as specified)	'Y' doc	ument of particular releva	ance; the claimed invention sive an inventive step when the	
other n		doc me	rument is combined with onts, such combination bei	one or more other such docu- ing obvious to a person stalled	
"P" docume later th	ent published prior to the international filing date but han the priority date claimed	ın t	the art. :ument member of the san	•	
Date of the	actual completion of the international search	Date	e of mailing of the interna	stional search report	
27	7 November 1995		08.12	. 9 5	
Name and m	nailing address of the ISA  European Patent Office, P.B. 5818 Patentiaan 2	Aut	honzed officer	<del></del>	
	NL - 2280 HV Ripmik Td. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax (+31-70) 340-3016		Stevnsborg, !	N	

Intr onal Application No
PCT/US 95/09834

		PC1/03 95/09634
C.(Continua	DOCUMENTS CONSIDERED TO BE RELEVANT	Relevant to claim No.
Category *	Citation of document, with indication, where appropriate, of the relevant passages	· ·
<b>A</b>	CH,A,680 788 (ALUSUISSE-LONZA SERVICES AG) 13 November 1992 see abstract	1
	see page 8, line 10 - line 32 see figures 7-11	
A	DE,A,39 26 466 (MESSERSCHMITT-BÖLKOW-BLOHM GMBH) 14 February 1991 see abstract see column 1, line 26 - column 2, line 6 see column 2, line 23 - line 26 see figures 1,2	
A	US,A,3 856 270 (FMC CORPORATION) 24 December 1974 see abstract see figures 1-4 see column 3, line 8 - column 4, line 35	<b>1</b>
A	EP,A,O 496 521 (HITACHI, LTD.) 29 July 1992 see the whole document	1
<b>A</b> _	US,A,5 320 139 (MILLIPORE CORPORATION) 14 June 1994 see abstract see column 4, line 5 - column 7, line 29 see figures	1
A	DATABASE WPI Section Ch, Week 8725, Derwent Publications Ltd., London, GB; Class J04, AN 87-175285 & JP,A,62 108 156 (SODO K.K.) 19 May 1987 see abstract; figures	

Int ional Application No PCT/US 95/09834

Publication date			Publication date
12-10-93	DE-A- DE-A- DE-D- EP-A- DE-U-	DE-A- 3825907 DE-D- 58907327 EP-A- 0347579	07-12-89 01-02-90 05-05-94 27-12-89 02-10-91
22-06-90	NONE		
13-11-92	NONE		
14-02-91	NONE		
24-12-74	NONE		
29-07-92	JP-A- US-A-	5223774 5344545	31-08-93 06-09-94
14-06-94	DE-T- EP-A- JP-A-	622115 0622115 7068154	28-09-95 02-11-94 14-03-95
	22-06-90 13-11-92 14-02-91 24-12-74 29-07-92	12-10-93  12-10-93  DE-A- DE-A- DE-D- EP-A- DE-U-  22-06-90  NONE  13-11-92  NONE  14-02-91  NONE  24-12-74  NONE  29-07-92  JP-A- US-A-  14-06-94  DE-T- EP-A-	date   member(s)

Form PCT/ISA/210 (patent family annex) (July 1992)

------

PCT WELTORGANISATION FOR GEISTIGES EIGENTUMInternationales Büro
INTERNATIONALE ANMELDUNG VERÖFFENTLICHT NACH DEM VERTRAG ÜBER DIE INTERNATIONALE ZUSAMMENARBEIT AUF DEM GEBIET DES PATENTWESENS (PCT)

(51) Internationale Patentklassifikation 6:

B01F 5/02, 5/06, B01J 19/24

(11) Internationale Veröffentlichungsnummer:

**WO 97/16239** 

A1

(43) Internationales Veröffentlichungsdatum:

9. Mai 1997 (09.05.97)

(21) Internationales Aktenzeichen:

PCT/EP96/03162

(22) Internationales Anmeldedatum:

18. Juli 1996 (18.07.96)

(81) Bestimmungsstaaten: CA, CN, JP, KR, US, europäisches Patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE,

IT, LU, MC, NL, PT, SE).

(30) Prioritätsdaten:

195 40 292.8

28. Oktober 1995 (28.10.95)

Veröffentlicht DE

Mit internationalem Recherchenbericht.

(71) Anmelder (für alle Bestimmungsstaaten ausser US): FORSCHUNGSZENTRUM KARLSRUHE **GMBH** [DE/DE]; Weberstrasse 5, D-76133 Karlsruhe (DE). BAYER AG [DE/DE]; D-51368 Leverkusen (DE).

(72) Erfinder; und

- (75) Erfinder/Anmelder (nur für US): SCHUBERT, Klaus [DE/DE]; Geigersbergstrasse 54, D-76227 Karlsruhe (DE). BIER, Wilhelm [DE/DE]; Grabener Weg 10, D-76344 Eggenstein-Leopoldshafen (DE). HERRMANN, Erhard [DE/DE]; Felix-von-Roll-Strasse 11, D-51375 Leverkusen (DE). MENZEL, Thomas [DE/DE]; Richrather Strasse 248, D-40723 Hilden (DE). LINDER, Gerd [DE/DE]; Stephan-Lochner-Weg 2, D-76149 Karlsruhe (DE).
- (74) Anwalt: RÜCKERT, Friedrich; Forschungszentrum Karlsruhe GmbH, Stabsabteilung Patente und Lizenzen, Weberstrasse 5, D-76133 Karlsruhe (DE).

(54) Title: STATIC MICROMIXER

(54) Bezeichnung: STATISCHER MIKROVERMISCHER

#### (57) Abstract

Disclosed is a static micromixer with a mixing chamber and a duct component upstream of the former for separate feeding to the mixing chamber of the fluids to be mixed or dispersed. The aim of the invention is to design the duct component in a static mixer of this generic type in such a way as to improve the efficiency of the mixing process in the mixing chamber. The invention is characterised by the following features: a) the wafer-like elements A and B for the duct component each consist of thin films with a thickness of 10-1000 microns, preferably < 250 microns, the lateral dimension being of the order of millimetres, a family of adjacent grooves being formed in each wafer-like element such that when the foils are superposed one on top of the other a separate series of channels is formed for feeding the fluids A' and B' to be mixed; b) the grooves have depths of less than 1000 microns, preferably less than 250 microns, widths of between I micron and the millimetre range but preferably less than 1000 microns, the wall thicknesses of the intermediate ridges and groove floors being less than 1000 microns and preferably less than 250 microns; c) each family of grooves in the stacked films follows an arc and lead alternately from the mixing chamber to a feed chamber for the fluid A' or B' in such a way that all families of grooves in the films are aligned parallel to one another and discharge into the mixing chamber.

#### (57) Zusammenfassung

Die Erfindung betrifft einen statischen Mikrovermischer mit einer Mischkammer und einem vorgeschalteten Führungsbauteil für die getrennte Zufuhr von zu mischenden oder zu dispergierenden Fluiden zu der Mischkammer. Die Erfindung hat zur Aufgabe, bei einem statischen Vermischer der gattungsgemäßen Bauart das Führungsbauteil für die getrennte Zufuhr der zu mischenden Fluide zur Mischkammer so zu gestalten, daß eine erhöhte örtliche und zeitliche Effektivität der Vermischung in der Mischkammer erzielt wird. Die Erfindung ist durch die folgenden Merkmale gekennzeichnet: a) die platternartigen Elemente A und B für das Führungsbauteil bestehen jeweils aus dünnen Folien mit einer Dicke von 10 bis 1000 µm, vorzugsweise < 250 µm, bei einer lateralen Ausdehnung im Millimeterbereich, in die je eine Schar benachbarter Nuten eingearbeitet ist, so daß beim Übereinanderschichten der Folien je eine Reihe von Kanälen für die Führung der zu mischenden Fluide A' und B' entsteht; b) die Nuten haben Tiefen von < 1000 µm, vorzugsweise < 250 µm, Breiten von 1 µm bis in den Millimeterbereich, vorzugsweise jedoch < 1000 μm, bei Wanddicken der Zwischenstege und Nutböden von < 1000 μm, vorzugsweise < 250 µm; c) die jeweiligen Scharen von Nuten in den übereinandergeschichteten Folien verlaufen jeweils bogenförmig gekrümmt und abwechselnd von der Mischkammer zu je einer Zufuhrkammer für das Fluid A' bzw. B' in der Weise, daß alle Scharen von Nuten der Folien parallel zueinander ausgerichtet in die Mischkammer ausmünden.

### LEDIGLICH ZUR INFORMATION

Codes zur Identifizierung von PCT-Vertragsstaaten auf den Kopfbögen der Schriften, die internationale Anmeldungen gemäss dem PCT veröffentlichen.

AM	Armenien	GB	Vereinigtes Königreich	MX	Mexiko
AT	Östeireich	GE	Georgien	NB	Niger
AU	Australien	GN	Guinea	NL	Niederlande
BB	Barbados ,	GR	Griechenland	NO	Norwegen
BE	Belgien	HU	Ungam	NZ	Neuseeland
BF	Burkina Faso	IE	Irland	PL	Polen
BG	Bulgarien	IT	Italien	PT	Portugal
BJ	Benin	JP	Japan	RO	Rumlinien
BR	Brasillen	KE	Kenya	RU	Russische Föderation
BY	Belarus	KG	Kirgieistan	SD	Sudan
CA	Kanada	KP	Demokratische Volksrepublik Korea	SE	Schweden
CF	Zentrale Afrikanische Republik	KR	Republik Korea	'SG	Singapur
CG	Kongo	KZ	Kasachstan	SI	Slowenien
CH	Schweiz	u	Liechtenstein	SK	Slowakei
CI	Côte d'Ivoire	· LK	Sri Lanka	SN	Senegal
CM	Kamerun	LR	Liberia	SZ	Swasiland
CN	China	LK	Litauen	TD	Tschad
CS	Tachechoslowakei	LU	Luxemburg	TG	Togo
CZ	Tachechiache Republik	LV	Lettland	TJ	Tadschikistan
DE	Deutschland	MC	Monaco	TT	Trinidad und Tobego
DK	Dinemark	MD	Republik Moldan	UA	Ukraine
EE	Estland	MG	Madagasker	UG	Uganda
ES	Spanien	ML	Mali	US	Vereinigte Staaten von Amerika
PI	Finnland	MN '	Mongolei	UZ	Usbekistan
FR	Frankreich	MR	Mauretanien	VN	Vietnam
GA	Gabon	MW	Malawi		

#### Statischer Mikrovermischer

------

Die Erfindung betrifft einen statischen Mikrovermischer mit einer Mischkammer und einem vorgeschalteten Führungsbauteil für die getrennte Zufuhr von zu mischenden oder zu dispergierenden Fluiden zu der Mischkammer gemäß dem Oberbegriff von Patentanspruch 1.

Aus der W091/16970 A1 (PCT/CH91/00109 v. 14.11.1991) ist eine Mischeranordnung in einer Kolonne mit Misch-, Katalysator-bzw. Kanalelementen bekannt, die in Schichten oder Lagen angeordnet sein können. Benachbarte Elemente innerhalb einer Lage oder Schicht sind gegeneinander zur Hauptströmungsrichtung geneigt angeordnet. Hierzu können die Elemente die Form eines schiefen Prismas haben, das von im Querschnitt quadratischen, gerade und parallel zueinander verlaufenden Kanälen durchzogen ist und das durch Zusammenfügen strukturierter Platten gefertigt werden kann. Bei einer so getroffenen Anordnung wird ein gleichmäßiger Strömungswiderstand bezüglich der zu mischenden Fluide erzielt, die Mischungseffektivität fällt jedoch vom Zentrum zu den Randzonen hin des als Mischkammer dienenden Kolonnenraumes am abströmseitigen Ende der Elemente stark ab.

Aus der DE 31 14 195 C2 ist eine gattungsgemäße Mischvorrichtung zur Vermischung strömender Medien mit mindestens zwei Einlaßkanälen, mit einem sich an diese anschließenden Kanalkörper sowie mit einem an die gemeinsame Auslaßseite des Kanalkörpers angeschlossenen Auslaßkanal bekannt. Der von Einzelkanälen durchzogene Kanalkörper, der zur getrennten Zufuhr der zu mischenden Medien zum Auslaßkanal dient, ist aus aufeinander aufgeschichteten Einzelwell-Einheiten aufgebaut, die aus je einer Trennwand und einem Wellbogen bestehen. Die Einzelkanäle jeder Einheit werden von den Wellungen des Wellbogens und der zugehörigen Trennwand gebildet. Die Einheiten sind so aufeinander geschichtet, daß die Einzelkanäle benachbarter Einheiten vorbestimmte Winkel zueinander bilden. In einem Ausführungsbeispiel ist die Anordnung so getroffen, daß

WO 97/16239 PCT/EP96/03162

- 2 -

der Kanalkörper gleich lange, parallele Einzelkanäle hat, wobei die Einzelkanäle der jeweiligen Einheiten abwechselnd an
je einen von zwei Einlaßkanälen angeschlossen sind, auf der
Auslaßseite des Kanalkörpers mit ihren Mündungen jedoch übereinander liegen. Da das jeweilige Medium nur in jeden zweiten
Einzelkanal, in der Höhenerstreckung des Kanalköpers gesehen,
einströmen darf, muß der Einlaß zu der jeweils dazwischenliegenden Einheit geschlossen sein (s. Spalte 6, Zeilen 26 bis 33
in Verbindung mit Fig. 7a, 7b), wodurch Totvolumina entstehen.
Aber auch bei dieser Bauart ergibt sich nur im Zentrum der
Auslaßseite des Kanalkörpers eine optimale Durchmischung; zu
den Randzonen hin nimmt die Mischungseffektivität ab. Auch ist
das Ausformen oder Anbringen der erforderlichen Einlaß-Verschlüsse aufwendig und stößt mit kleiner werdenden Kanalquerschnitten auf fertigungstechnische Schwierigkeiten.

Ausgehend von dem vorstehend erörteten Stand der Technik hat die Erfindung zur Aufgabe, bei einem statischen Vermischer der gattungsgemäßen Bauart das Führungsbauteil für die getrennte Zufuhr der zu mischenden Fluide zur Mischkammer so zu gestalten, daß eine erhöhte örtliche und zeitliche Effektivität der Vermischung in der Mischkammer erzielt wird. Darüber hinaus soll der Vermischer hinsichtlich der Kanäle in dem Führungsbauteil eine vakuumdichte und druckfeste Ausführung ermöglichen, so daß er insbesondere in der chemischen Technik eingesetzt werden kann.

Diese Aufgabe wird mit den kennzeichnenden Merkmalen von Patentanspruch 1 gelöst. Die hierauf bezogenen Unteransprüche beinhalten vorteilhafte Weiterbildungen dieser Lösung.

Durch die bogenförmig gestalteten, parallel zueinander und zur Hauptströmungsrichtung in die Mischkammer ausmündenden Kanäle der Elemente A und B des Führungsbauteils wird über dem gesamten Ausströmquerschnitt eine gleichmäßig hohe Vermischung bei Vermeidung von Totvolumina im Führungsbauteil erzielt. Aufgrund der Mikrostrukturierung der Kanalreihen werden die zu

vermischenden oder zu dispergierenden Fluide in eine Vielzahl feinster benachbarter Stromfäden oder Lamellen unterteilt, die beim Eintritt in die Mischkammer sich auf schnellstem und kürzestem Wege durchmischen können oder in eine Tropfen oder Blasen bildende Dispersphase und eine die kontinuierliche Phase bildende Hüllphase zerteilt werden. Die Dichte der Kanalmündungen und damit der Stromfäden am Eintritt in die Mischkammer beträgt einige tausend Mündungen bzw. Stromfäden pro cm<sup>2</sup>.

Ein Ausführungsbeispiel des erfindungsgemäßen Mikrovermischers sowie ein Verfahren zur Herstellung desselben werden im folgenden anhand der Zeichnungen erläutert.

Die Figur 1 zeigt perspektivisch und in starker Vergrößerung zwei übereinander zu schichtende, genutete Folien und eine Deckplatte;

die Figur 2 zeigt den Mikrovermischer schematisch in der Draufsicht;

die Figur 3 veranschaulicht das Herstellungsverfahren für die genuteten Folien.

Gemäß Fig. 1 bestehen die plattenförmigen, übereinanderzuschichtenden Elemente abwechselnd jeweils aus dünnen Folien 1A und 1B mit einer Dicke von 30 bis 1000  $\mu$ m, vorzugsweise < 250  $\mu$ m bei einer lateralen Ausdehnung im Millimeterbereich. In die Folien 1A, 1B ist je eine Schar eng benachbarter, bogenförmig gekrümmter Nuten 2A, 2B eingearbeitet, so daß beim Übereinanderschichten der Folien 1A, 1B abwechselnd je eine Reihe von Kanälen 3A und 3B entsteht (siehe Fig. 2).

Die Nuten haben Tiefen von < 1000  $\mu$ m, vorzugsweise < 250  $\mu$ m, Breiten von 10  $\mu$ m bis in den Millimeterbereich, vorzugsweise jedoch < 500  $\mu$ m, bei Wanddicken der Zwischenstege 4A, 4B und Nutböden 5A, 5B von < 1000  $\mu$ m, vorzugsweise < 250  $\mu$ m. Die

Nutenschar 2B verläuft von der linken, hinteren Stirnfläche 6B bogenförmig zum mittleren Bereich 6C der vorderen Stirnfläche 8B der Folie 1B, die Nutenschar 2A verläuft bogenförmig von der rechten, hinteren Stirnfläche 6A zum mittleren Bereich 6C der vorderen Stirnfläche 8A der Folie 1A, wobei beide Folienarten 1A und 1B den gleichen Grundriß haben. Dieser Grundriß hat die geometrische Form eines Fünfecks, gebildet aus einem Rechteck mit hieran angeschlossenem, gleichschenkeligem Dreieck, wobei eine Seite des Rechtecks die Grundseite des gleichschenkeligen Dreiecks bildet.

Schichtet man eine Vielzahl dieser Folien 1A und 1B abwechselnd und deckungsgleich übereinander, so entsteht ein
Führungsbauteil 6, wie es in der Draufsicht schematisch aus
Fig. 2 hervorgeht. An die beiden von den Schenkeln des Dreiecks gebildeten Flächen 6A, 6B sind die Zufuhrkammern 7A, 7B
für die Fluide A', B' angeschlossen. An den mittleren Bereich
6C der gegenüberliegenden Fläche 8, in den die Kanäle 3A, 3B
parallel zueinander ausgerichtet ausmünden, ist die Mischkammer 9C angeschlossen, über die die miteinander zu vermischenden oder zu dispergierenden Fluide A', B' bzw. deren
Reaktionsprodukte C' abgeführt werden.

Die Schenkelflächen 6A, 6B sind gegenüber der Fläche 8 bzw. den beiden Seitenflächen 10, 11 des Führungsbauteils 6 so geneigt, daß die vom mittleren Bereich 6C der Fläche 8, an den die Mischkammer 9C angeschlossen ist, ausgehenden, von Folie 1A zu Folie 1B abwechselnd zu der Zufuhrkammer 7A und der Zufuhrkammer 7B führenden Scharen von bogenförmigen Kanälen 3A bzw. 3B annähernd gleiche Längen aufweisen.

Bei kreisbogenförmigen Nuten bzw. Kanälen bedeutet dies, daß die Bogenlänge

$$L = \frac{2\pi r \cdot \alpha}{360^{\circ}} = const.$$

sein soll, wobei r den jeweiligen Krümmungsradius und α den zugehörigen Bogenwinkel der betreffenden Nuten bzw. Kanäle bedeutet. Dies würde an sich zu gekrümmten Schenkelflächen 6A, 6B führen. In der Praxis ist es jedoch im allgemeinen ausreichend, diese gekrümmten Flächen durch eine Näherungsgerade "einzuebnen", z. B. nach der Vorschrift

$$\frac{\alpha_2}{\alpha_1} = \frac{r_1}{r_2}$$

wobei  $r_1$  den größten und  $r_2$  den kleinsten Radius und  $\alpha_1$  bzw.  $\alpha_2$  die zugehörigen Bogenwinkel zur äußersten und innersten Nutbedeuten.

Nach dem Übereinanderschichten werden die Folien 1A, 1B mit Deckplatten 15 versehen und vakuumdicht und druckfest miteinander verbunden, z. B. diffusionsverschweißt, so daß das so entstandene Führungsbauteil 6 die Gestalt eines homogenen Mikrostrukturkörpers erhält, der an die Kammern 7A, 7B und 9C angeschlossen wird.

Zur Herstellung der Folien 1A, 1B kann eine drehbare Sintermetallplatte 12 mit geschliffener Oberfläche eingesetzt werden, auf der eine Rohfolie 13 aus einem Metall wie z. B. Kupfer oder Silber mittels Unterdruck aufgespannt wird (siehe Fig. 3). In die sich drehende Rohfolie 13 werden mittels einem Formdiamanten (nicht dargestellt) in einem mittleren Bereich zwischen Drehmittelpunkt M und Peripherie der Rohfolie 13 eine Schar konzentrischer Nuten 14 eingearbeitet. Sodann wird die Rohfolie 13 in vier Einzelfolien 1A, 1B unterteilt in der Weise, daß vier mit dem mittleren Durchmesser der konzentrischen Nutenschar übereinstimmende Längsseiten 8, von deren mittlerem Bereich die kreisbogenförmige Nutenschar 14 ihren Ausgang nimmt, je zwei, also insgesamt acht Schmalseiten 10. 11 sowie je zwei Schenkelpaare 6A, 6B entstehen, wobei die Nutenschar 14 jeweils in einen der beiden Schenkel 6A bzw. 6B ausmündet. Es entstehen also aus vier Segmenten die vorerwähnten vier deckungsgleichen Fünfecke. Die Nuten haben vorzugsWO 97/16239 PCT/EP96/03162

- 6 -

weise rechteckige Querschnitte. Es können auch mehrere genutete Rohfolien übereinander geschichtet und gemeinsam in die Fünfecke zerschnitten werden.

### Bezugszeichenliste

- 1A Folie
- 1B Folie
- 2A Nuten
- 2B Nuten
- 3A Kanäle
- 3B Kanäle
- 4A Zwischenstege
- 4B Zwischenstege
- 5A Nutböden
- 5B Nutböden
- 6 Führungsbauteil
- 6A hintere Stirnfläche
- 6B hintere Stirnfläche
- 6C mittlerer Bereich
- 7A Zufuhrkammer
- 7B Zufuhrkammer
- 8 vordere Stirnfläche
- 9C Mischkammer
- 10 Seitenflächen
- 11 Seitenflächen
- 12 Sintermetallplatte
- 13 Rohfolie
- 14 Nuten
- 15 Deckplatte
- A' Fluide
- B' Fluide
- C' Reaktionsprodukt
- r<sub>1</sub> Krümmungsradius
- r<sub>2</sub> Krümmungsradius
- a<sub>1</sub> Bogenwinkel
- $\alpha_2$  Bogenwinkel
- M Drehmittelpunkt

#### Patentansprüche:

- Statischer Mikrovermischer mit einer Mischkammer und einem vorgeschalteten Führungsbauteil für die getrennte Zufuhr von zu mischenden oder zu dispergierenden Fluiden zu der Mischkammer, wobei
  - das Führungsbauteil aus mehreren, plattenartigen, übereinandergeschichteten Elementen zusammengesetzt ist, die von je einer Reihe langgestreckter, benachbart zueinander verlaufender Kanäle durchzogen sind;
  - dabei sind wenigstens zwei Arten von Elementen A und B vorgesehen, die abwechselnd übereinandergeschichtet sind und deren Reihen von Kanälen mit ihren an die Mischkammer angrenzenden Mündungen übereinander liegen und dort einen gemeinsamen Querschnitt bilden, wobei abwechselnd die Reihen von Kanälen der Elementart A zu einer Zufuhrkammer eines Fluids A' und die Reihen von Kanälen der Elementart B zu einer Zufuhrkammer eines Fluids B' führen, gekennzeichnet durch folgende Merkmale:
  - a) die plattenartigen Elemente A und B für das Führungsbauteil bestehen jeweils aus dünnen Folien (1A, 1B) mit einer Dicke von 30 bis 1000  $\mu$ m, vorzugsweise < 250  $\mu$ m, bei einer lateralen Ausdehnung im Millimeterbereich, in die je eine Schar benachbarter Nuten (2A, 2B) eingearbeitet sind, so daß beim Übereinanderschichten der Folien (1A, 1B) je eine Reihe von Kanälen (3A, 3B) für die Führung der zu mischenden Fluide A' und B' entsteht;
  - b) die Nuten (2A, 2B) haben Tiefen von < 1000  $\mu$ m, vorzugsweise < 250  $\mu$ m, Breiten von 10  $\mu$ m bis in den Millimeterbereich, vorzugsweise jedoch < 500  $\mu$ m, bei Wanddicken der Zwischenstege (4A, 4B) und Nutböden (5A, 5B) von < 1000  $\mu$ m, vorzugsweise < 250  $\mu$ m;
  - c) die jeweiligen Scharen von Nuten (2A, 2B) in den übereinandergeschichteten Folien 1A, 1B verlaufen jeweils bogenförmig gekrümmt und abwechselnd von der Mischkammer (9C) zu je einer Zufuhrkammer (7A, 7B) für das Fluid A' bzw. B' in der Weise, daß alle Scharen von


Nuten (2A, 2B) der Folien 1A, 1B parallel zueinander ausgerichtet in die Mischkammer (9C) ausmünden.

- 2. Statischer Mikrovermischer nach Anspruch 1, gekennzeichnet durch folgende Merkmale:
  - a) die übereinandergeschichteten Folien 1A, 1B haben in der Draufsicht die geometrische Form eines Fünfecks, das durch ein Rechteck mit hieran angeschlossenem gleichschenkeligem Dreieck gebildet wird, wobei eine Seite des Rechtecks die Grundseite des gleichschenkeligen Dreiecks bildet;
  - b) an die beiden von den Schenkeln des Dreiecks gebildeten Flächen (6A, 6B) sind die Zufuhrkammern (7A, 7B) für die Fluide A' bzw. B' und an die von der gegenüberliegenden Längsseite des Rechtecks gebildete Fläche (8) die Mischkammer (9C) angeschlossen,
  - c) die Schenkel (6A, 6B) des Dreiecks sind gegenüber seiner Grundseite so geneigt, daß die von der Mischkammer (9C) ausgehenden, von Folie (1A) zu Folie (1B) abwechselnd zu der Zufuhrkammer (7A) bzw. der Zufuhrkammer (7B) führenden bogenförmigen Nuten (2A, 2B) jeweils annähernd gleiche Längen aufweisen.
- 3. Statischer Mikrovermischer nach Anspruch 1, dadurch gekennzeichnet, daß die übereinandergeschichteten Folien (1A, 1B) zu einem vakuumdichten und druckfesten Mikrostrukturkörper (6) miteinander verbunden, z. B. diffusionsverschweißt, sind, der an die Zufuhrkammer (7A bzw. 7B) und die Mischkammer (9C) angeschlossen ist.
- 4. Verfahren zur Herstellung der Folien nach Anspruch 2, gekennzeichnet durch folgende Schritte:
  - a) eine Rohfolie (13) wird mittels Unterdruck auf eine drehbare, geschliffene Metallsinterplatte (12) gespannt;
  - b) in die sich drehende Rohfolie (13) werden mittels einem Formdiamanten in einem mittleren Bereich der Rohfolie (13) zwischen deren Drehmittelpunkt (M) und deren Peri-


- pherie eine Schar konzentrischer Nuten (14) eingearbeitet;
- c) die Rohfolie (13) wird in vier Einzelfolien (1A, 1B) unterteilt in der Weise, daß durch zwei aufeinander senkrecht stehende, sich im Drehmittelpunkt (M) kreuzende Schnitte vier Segmente entstehen, und daß durch weitere Schnitte an jedem Segment vier deckungsgleiche Fünfecke gemäß Anspruch 2 gebildet werden.

1/2

Fig. 1



2/2



Inte mal Application No PCT/EP 96/03162

A. CLAS IPC 6	sification of subject matter B01F5/02 B01F5/06 B01J1	9/24	
According	to International Patent Classification (IPC) or to both national cl	assification and IPC	
	DS SEARCHED		
	documentation searched (classification system followed by classification system followed system followed by classification system followed by	(ication symbols)	
IPC 6		<b>,</b> ,	-
Document	ation searched other than minimum documentation to the extent t	hat such documents are included in the fields	searched
Electronic	data base consulted during the international search (name of data	base and, where practical, search terms used	)
C. DOCUM	MENTS CONSIDERED TO BE RELEVANT		<del></del>
Category *	Citation of document, with indication, where appropriate, of the	e relevant passages	Relevant to claim No.
A,P	WO,A,95 30476 (BAYER AG, FORSCH KALSRUHE GMBH) 16 November 1995 see the whole document	UNGSZENTRUM	1-4
A	PATENT ABSTRACTS OF JAPAN vol. 6, no. 149 (C-118), 10 Augu & JP,A,57 071627 (TEIJIN LTD), see abstract	ust 1982 4 May 1982,	1
A	WO,A,94 21372 (E.I.DU PONT DE N COMPANY) 29 September 1994 see claims 1,21,28	EMOURS AND	1,4
A	WO,A,91 16970 (GEBRÜDER SULZER A November 1991 cited in the application see claims 1-12	AG) 14	1
		-/	,
		-/	
	<u> </u>		
X Furt	ther documents are listed in the continuation of hox C.	X Patent family members are listed	in annex.
* Special ca	Regones of cited documents :	T later document published after the int	
	ent defining the general state of the art which is not lered to be of particular relevance	or priority date and not in conflict w cited to understand the principle or t	
'E' earlier	document but published on or after the international	invention "X" document of particular relevance; the	claimed invention
filing of "L" docum	ent which may throw doubts on priority claim(s) or	cannot be considered novel or canno involve an inventive step when the de	
which	is cited to establish the publication date of another n or other special reason (as specified)	'Y' document of particular relevance; the cannot be considered to involve an ir	
'O' docum	ent referring to an oral disclosure, use, exhibition or means	document is combined with one or in ments, such combination being obvio	ore other such docu-
"P" docum	ent published prior to the international filing date but han the priority date claimed	in the art.  *& document member of the same patent	
	actual completion of the international search	Date of mailing of the international se	
2	9 October 1996	26.11.96	
Name and r	mailing address of the ISA	Authorized officer	
	European Patent Office, P.B. 5818 Patentiaan 2 NL - 2280 HV Rupingh Tel. (- 31-70) 340-2040, Tx. 31 651 epo nl, Fair (- 31-70) Mn. 1014	Cordero Alvarez.	M

Form PCT ISA'218 (second sheet) (July 1992)

٠ 1

tnu mai Application No PCT/EP 96/03162

		PCT/EP 96/03162		
	auon) DOCUMENTS CONSIDERED TO BE RELEVANT		. Belower to the tri	
Category *	Citation of document, with indication, where appropriate, of the relevant passages		Relevant to claim No.	
A	GB,A,2 073 604 (AKTIEBOLAGET CARL MUNTERS) 21 October 1981 cited in the application see claims; figures & DE,A,31 14 195 cited in the application		1	
			,	
			·	
			,	

1

------

Form PCT-ISA-218 (continuation of second sheet) (July 1992)

information on patent family members

Inte mal Application No PCT/EP 96/03162

Patent document cited in search report	Publication date		nt family nber(s)	Publication date
WO-A-9530476	16-11-95	DE-A-	4416343	16-11-95
		DE-A-	4433439	21-03-96
		WO-A-	9530475	16-11-95
WO-A-9421372	29-09-94	US-A-	5534328	09-07-96
	,	AU-A-	6409794	11-10-94
		BR-A-	9405989	26-12-95
		EP-A-	0688242	27-12-95
•		JP-T-	8508197	03-09-96
WO-A-9116970	14-11-91	EP-A-	0482145	29-04-92
		JP-T-	4506767	26-11-92
		US-A-	5320428	14-06-94
GB-A-2073604	21-10-81	SE-B-	432059	19-03-84
		DE-A-	3114195	28-01-82
		FR-A-	2480135	16-10-81
		JP-C-	1582172	11-10-90
		JP-B-	2005448	02-02-90
		JP-A-	56158134	05-12-81
		SE-A-	8002770	12-10-81

# INTERNATIONALER RECHERCHENBERICHT

Inter nates Aktenzeichen PCT/EP 96/03162

IPK 6	B01F5/02 B01F5/06 B01J19	/24	
1	·		
	nternationalen Patentklassifikation (IPK) oder nach der nationalen ERCHIERTE GEBIETE	Klassifikation und der IPK	
Recherchie	erter Mindestprufstoff (Klassifikationssystem und Klassifikationssyr BO1F BO1J BO1L	mbole )	
IPK 6	BOIF BOID BOIL		
Recherchie	rte aber nicht zum Mindestprufstoll gehorende Veröffentlichungen,	soweit diese unter die recherchierten Gebi	ete failen
ľ	·		
Wanrend o	er internationalen Recherche konsultierte elektronische Datenbank (	(Name der Datenbank und evil, verwendet	e Suchbegnile)
C. ALS W Kategorie	ESENTLICH ANGESEHENE UNTERLAGEN  Bezeichnung der Veröffentlichung, soweit erforderlich unter Ange	she dee in Retracht turnmenden Teile	Betr. Anspruch Nr.
tezugare	Decidency and resolutionally, where thousands and religion	and the productive control of the	bev. Amproch Ar.
A,P	WO,A,95 30476 (BAYER AG, FORSCHU	NGSZENTRUM	1-4
	KALSRUHE GMBH) 16.November 1995 siehe das ganze Dokument		
A	PATENT ABSTRACTS OF JAPAN vol. 6, no. 149 (C-118), 10.Augu:	st 1982	1
	& JP,A,57 071627 (TEIJIN LTD), 4 siehe Zusammenfassung	.Mai 1982,	
A	WO,A,94 21372 (E.I.DU PONT DE NE COMPANY) 29.September 1994	MOURS AND	1,4
	siehe Ansprüche 1,21,28		
Α	WO,A,91 16970 (GEBRÜDER SULZER AG	G)	1
	14.November 1991 in der Anmeldung erwähnt		
	siehe Ansprüche 1-12		
	-i-	-/	
		,	
	ere Veroffentlichungen sind der Fortsetzung von Feld C zu ihrnen	X Siehe Anhang Patentiamilie	
'A' Veröffe	Kategorien von angegebenen Veroffentlichungen : intlichung, die den allgemeinen Stand der Fechnik delimert,	"T" Spatere Veroffentlichung, die nach den oder dem Priontatsdatum veroffentlich Anmeldung nicht kollidiert, sondern n	it worden ist und mit der
E' álteres	icht als besonders bedeutsam anzusehen ist Dohument, das jedoch erst am oder nach dem internationalen dedatum veroffentlicht worden ist	Erfindung zugrundehegenden Prinzips Theorie angegeben ist	oder der ihr zugrundeliegenden
"L" Veröffe	ntdichung, die geegnet ist, einen Prioritatianspruch zweiselhaft er- m zu lassen, oder durch die das Verossentichungsdatum einer	"X" Veröffentlichung von besonderer Bedei kann allein aufgrund dieser Veröffentli erfindenscher Tatigkeit berühend betri	chung meht als neu oder auf
andere soll od	n im Recherchenbenicht genannten Veröllentlichung helegt werden er die aus einem anderen besonderen Grund angegeben ist (wie	"Y" Veröffentlichung von besonderer Bede kann nicht als auf erfinderischer Tatig	itung; die beanspruchte Erfindung
	mes) mitichung, die sich auf eine mundliche Offenbarung, mutzung, eine Ausstellung oder andere Maßnahmen bezieht	werden, wenn die Veroffentlichung mi Veröffentlichungen dieser Kategorie ir diese Verbindung für einen Fachmann	Verbindung gebracht wird und
"P" Veröffe	ntlichung, die vor dem internationalen Anmeldedatum, aber nach eanspruchten Prioritätsdatum veröffentlicht worden ist	'&" Veröffendichung, die Mitglied derselb	
Datum des /	Abschlusses der internationalen Recherche	Absendedatum des internationalen Rei	therchenberichts
29	9.0ktober 1996	26	.11.96
Name und F	Postanschrift der Internationale Recherchenbehorde	Bevollmachtigter Bediensteter	
	Europäisches Patentami, P.B. 5818 Patentiaan 2 NL - 2280 HV Ripwijk Tel. (~ 31-70) 340-2040, Tx. 31 651 epo nl.	Condona Al.	<u>,                                    </u>
	Fax: ( - 31-70) 340-3016	Cordero Alvarez,	n i

1

### INTERNATIONALER RECHERCHENBERICHT

Inte males Aktenzeichen
PCT/EP 96/03162

	· · ·	PCI/EP 9	0/03105
C.(Fortsetz)	ng ALS WESENTLICH ANGESEHENE UNTERLAGEN		
Kategorie*	Bezeichnung der Veröffentlichung, soweit erforderlich unter Angabe der in Betracht komm	nenden Teile	Betr. Anspruch Nr.
A	GB,A,2 073 604 (AKTIEBOLAGET CARL MUNTERS) 21.0ktober 1981 in der Anmeldung erwähnt siehe Ansprüche; Abbildungen & DE,A,31 14 195		1
	in der Anmeldung erwähnt		
	•		
		į	
	•		
	·	·	
į			

1

## INTERNATIONALER RECHERCHENBERICHT

Angaben zu Veroffentlich....gen, die zur selben Patentfamilie gehoren

Inte shales Aktonomehen
PCT/EP 96/03162

Im Recherchenbericht ngeführtes Patentdokument	Datum der Veroffentlichung	Mitglied(er) der Patent/amilie  DE-A- 4416343 DE-A- 4433439 WO-A- 9530475		Datum der Veröffentlichung
WO-A-9530476	16-11-95			16-11-95 21-03-96 16-11-95
WO-A-9421372	29-09-94	US-A- AU-A- BR-A- EP-A- JP-T-	5534328 6409794 9405989 0688242 8508197	09-07-96 11-10-94 26-12-95 27-12-95 03-09-96
WO-A-9116970	14-11-91	EP-A- JP-T- US-A-	0482145 4506767 5320428	29-04-92 26-11-92 14-06-94
GB-A-2073604	21-10-81	SE-B- DE-A- FR-A- JP-C- JP-B- JP-A- SE-A-	432059 3114195 2480135 1582172 2005448 56158134 8002770	19-03-84 28-01-82 16-10-81 11-10-90 02-02-90 05-12-81 12-10-81